

## **PRODUCT INSTRUCTION SHEET**

### **REFERENCE**

Adjustable Height Perching Stool with Padded Back and Tubular Arms  
Product Codes: 506B / 506W / 706PU

### **DESCRIPTION**

Practical perching stool manufactured in high grade tensile steel with a tough nylon coating. All models have front to back struts for additional strength. Both seats and backs are padded - the seats are angled for improved posture. Seats and backs are available in either heat sealed PVC or PU (polyurethane).

### **TECHNICAL SPECIFICATIONS**

Seat Height Min:	53cm (21")
Seat Height Max:	69cm (27")
Width:	58cm (23")
Depth:	41cm (16")
Seat Width:	34cm (13")
Seat Depth:	28cm (11")
Back size:	10 ½" x 6" (267mm x 152mm)



### **USAGE REQUIREMENTS**

1. Do not exceed recommend weight of 165kg (26 Stone)
2. Before, during and after use, ensure that seat fixing screws are secure.
3. The product is not designed to be "swung on" either in a backward, sideways or forward motion.
4. The 4 ferrules must be in contact with the ground at all times. Use on level surfaces only.
5. When adjusting the legs, ensure that there is no gap between horseshoe clip and frame. The clip spindle must be fully located right through to the outside frame.
6. Clean frame with cream cleaner, upholstery with soap and water.
7. Ensure there is no damage to frame coating and check there are no gaps on upholstery welds.